

# Namron Alfa reflektor Pro matt hvit



## El.nr 3220293

EAN: 7070990336512



### Teknisk beskrivelse

|                                    |   |
|------------------------------------|---|
| Lyskilde type                      | Integrert ikke utskiftbar LED chip 8,3W |
| Total effekt inkl driver           | 10W                                     |
| Optikk                             | Reflektor                               |
| Lumen LED chip (lm)                | 845                                     |
| Lumen system (lm)                  | 760                                     |
| Kelvin                             | 2700                                    |
| RA indeks                          | 98                                      |
| SDCM                               | ≤ 3                                     |
| Spredning                          | 35°                                     |
| Dimbar                             | Ja                                      |
| Dimmetype                          | Faseavsnitt                             |
| Tiltbar                            | Ja – 30°                                |
| Temperaturområde/maks Ta           | 50°C                                    |
| Levetid L70B50/L90B10 ved 25°C (t) | 120.000/50.000                          |
| Spenning (driver)                  | 230V                                    |
| Isolasjonsklasse                   | II – SELV                               |
| Kapslingsklasse                    | IP44                                    |
| Energiklasse                       | F                                       |
| Materiale                          | Støpt aluminium                         |
| Farge                              | Matt hvit – RAL 9003                    |
| Montering                          | Innfelt                                 |
| Innfellingsdiameter (mm)           | 83                                      |
| Diameter (mm)                      | 95                                      |
| Høyde (mm)                         | 48                                      |
| Maks antall pr sikring (10A B)     | 115                                     |
| Vedlikehold                        | Rengjøres med fuktig klut               |



IP44

